

# POWERSPORTS

## OWNER'S MANUAL

**Always wear a helmet it could save your life!**  
**This Go-kart is designed for operators age 13 and over. Adult supervision is required for riders age 16 and under**



**Model: GK008, FR100GK**

**READ THIS MANUAL CAREFULLY!**

**Provincial / Municipal governments have different regulations pertaining to owning and operating an off-road vehicle, learn the regulations in your area.**

# **To the Owner**

Congratulations on your purchase of a GK008/FR100GK Go Kart. This Owner's/Operator's manual will provide you information regarding safe operation, operational instructions, maintenance and care. Fully understanding this manual and following all of the instructions herein will provide the knowledge needed to have safe and enjoyable Go Kart operation.

## **Safety - Notice to parents**

The recommended age for operating this Go Kart is 13 and over. Even though a child may meet the minimum recommended age, children differ in skills, physical abilities, and judgement. Some children may not be able to operate the Go Kart safely. Parents should permit continued use only if they determine that the child has the ability to operate the Go Kart in a safe manner.

**THIS Go Kart IS NOT A TOY AND COULD BE HAZARDOUS TO OPERATE. A Go Kart handles differently from other vehicles including motorcycles and cars. A collision or rollover can occur quickly, even during routine maneuvers such as turning, driving on hills and over obstacles.**

## **Reading the Owner's/ Operator's Manual**

It is important this manual is read from cover to cover carefully by the Go Kart owner and all operators. Parents should review the manual carefully with their children. Never allow anyone to operate the Go Kart without first reading and understanding the Owner's/Operator's manual.

This Owner's/ Operator's manual should be a permanent part of the Go Kart and should remain with the vehicle at all times. The manual should also remain with the vehicle if sold.

To emphasize special important information in the manual, please note the following :



This is the alert symbol. The symbol means **ATTENTION!**, **BECOME ALERT!**

To emphasize important safety information, the word **WARNING**, with the alert symbol, has special meaning:



Indicates a potential hazard that could result in **SEVERE INJURY** or **DEATH** to the operator, bystander or person repairing the go-kart.

To emphasize important information, the word **CAUTION** has special meaning:

**CAUTION:**

Indicates special precautions that must be taken to avoid damage to the Go Kart.

To emphasize important information, the word **NOTE** has special meaning:

**NOTE:**

Indicates key information to make procedures easier or clearer to understand.

|                                                                                                                    |
|--------------------------------------------------------------------------------------------------------------------|
|  <b>WARNING</b> or <b>CAUTION</b> |
| The first part will identify a <b>POTENTIAL HAZARD</b> .                                                           |
| The second part will describe <b>WHAT COULD HAPPEN</b> if the warning or caution is ignored.                       |
| The third part will describe <b>HOW TO AVOID THE HAZARD</b> .                                                      |

We are concerned about the environment and believes in conserving and protecting all natural resources. For this reason, owners should recycle, trade in, or dispose as appropriate, oil and tires.



This manual is based on the latest product information available at the time of publication. We have a policy of continually improving its products. Due to improvements, or other changes, there may be some discrepancies. We reserve the right to make product changes at any time, without notice and without incurring any obligation to make the same or similar changes to vehicles previously built or sold.

## **WARNING**

Operating, servicing and maintaining a passenger vehicle or off-road vehicle can expose you to chemicals including engine exhaust, carbon monoxide, phthalates, and lead, which are known to the state of California to cause cancer and birth defects or other reproductive harm. To minimize exposure, avoid breathing exhaust, do not idle the engine except as necessary, service your vehicle in a well-ventilated area and wear gloves or wash your hands frequently when servicing your vehicle. For more information go to [www.P65Warnings.ca.gov/passenger-vehicle](http://www.P65Warnings.ca.gov/passenger-vehicle)

# IMPORTANT LABELS

## LOCATION



# IMPORTANT LABELS

## WARNING LABELS

1

### WARNING

THIS GO-KART CAN BE HAZARDOUS TO OPERATE IF DRIVEN CARELESSLY. INJURIES CAN RESULT IF YOU DO NOT FOLLOW THESE INSTRUCTIONS:

- READ OWNER'S MANUAL AND ALL LABELS BEFORE YOU OPERATE THIS GO-KART.
- NEVER OPERATE THIS GO-KART WITHOUT PROPER INSTRUCTIONS. Beginners require mature supervision.
- NEVER OPERATE THIS GO-KART ON PUBLIC ROADS. It is intended for off-road use only.
- NEVER OPERATE THIS GO-KART AT EXCESSIVE SPEEDS.
- NEVER ATTEMPT WHEELIES, JUMPS, OR OTHER STUNTS.

6

### WARNING

Improper tire pressure or overloading can cause loss of control. Loss of control can result in severe injury or death.

- Cold tire pressure:  
Front:  $14 \pm 1$  psi ( $96.5 \pm 7$  kpa)  
Rear:  $14 \pm 1$  psi ( $96.5 \pm 7$  kpa)
- Maximum weight capacity is 150 lbs. (68 kg)

2

### WARNING

FAILING TO TIE UP LONG HAIR COULD RESULT IN HAIR GETTING CAUGHT IN MOVING PARTS RESULTING IN SEVERE INJURY OR DEATH



ALL HAIR MUST BE TIED UP ABOVE SHOULDER LENGTH.  
ALL LOOSE CLOTHING MUST BE SECURED.  
ALL NECKLACES AND SCARVES MUST BE SECURED

7

### WARNING



Never touch engine or exhaust after running engine until they have cooled.

8

### WARNING



Keep hands and fingers away from chains and sprockets.  
Make sure guards are securely in place before operation.

3

### WARNING

ALWAYS WEAR SEAT BELT WHILE OPERATING THIS VEHICLE.  
KEEP HANDS, ARMS, FEET AND LEGS IN THE VEHICLE AT ALL TIMES.

9

### WARNING



DO NOT RIDE ON BACK OF VEHICLE

4

### WARNING



The recommended minimum age to operate this vehicle is 13. Continual adult supervision is required for riders under 16.

5


### WARNING

THIS GO-KART IS DESIGNED FOR ONE OPERATOR AND NO PASSENGERS.




# SAFETY

1. Always read and understand the Owner's/Operator's manual and warnings before starting the Go Kart for the first time
2. This Go Kart should only be assembled by someone who has the knowledge, ability and skills to read and understand mechanical instructions.
3. Use caution when providing maintenance on this Go Kart. Make sure engine is turned off and all components are cool. Never attempt to make any adjustments while engine is running.
4. Do not modify this Go Kart in any way, modifications could make the Go-Kart unsafe and/or in violation of Federal and State laws.
5. This Go Kart is recommended for riders 13 and older.
6. Always wear a certified DOT motorcycle or ATV helmet that fits properly.
7. This Go Kart is designed for one operator and no passengers.
8. Always wear seat belt provided. Make sure seat belts fit properly before starting the Go Kart.
9. Never operate this Go Kart on paved surfaces and/or public roads. Pavement may cause the Go Kart to become unstable.
10. The head bar in back of the operator is not intended to provide rollover protection. Before each use, make sure all tubes are securely in place and bolts are tight.
11. Never operate Go Kart with long hair, loose jewelry or loose clothing that could get caught in moving parts.
12. Always go slow on unfamiliar terrain. Be alert to changing terrain conditions when operating the Go Kart.
13. Never take drugs or alcohol before or during operation of this Go Kart.
14. Never attempt jumps or any other type of stunts while operating this Go Kart.
15. Always follow the Pre-ride inspection procedures and maintenance procedures located in this manual before use.
16. Always go slow on terrain that is not familiar, be alert, an obstacle could come up unexpectedly.
17. Always keep hands, arms, legs and feet inside the Go Kart at all times.
18. Never operate Go Kart in water that is deeper than 2 inches. Do not operate in fast flowing water. Water can affect braking performance of the Go Kart. Check braking performance after exposure to water, it may be necessary to apply the brakes allowing friction to dry out the pads.
19. Do not attempt to fill the Go-Kart with gasoline while the engine is running or the engine is hot.


# DESCRIPTIONS AND PART LOCATIONS



1. Front tires
2. Plastic nose piece
3. Net
4. Head bracket assembly
5. Clutch assembly cover
6. Rear tires
7. Side panel
8. Seat
9. Seat belt
10. Steering wheel
11. Gas pedal
12. Brake pedal
13. Brake fluid reservoir
14. Tie rods
16. Rear brake caliper
17. Rear axle
18. Drive chain
19. Fuel tank cap
20. Fuel tank
21. Pull start cord
22. Air filter housing
23. Muffler
24. Choke lever
25. Fuel Valve
26. Oil fill plug / Dipstick
27. Oil drain screw



# DESCRIPTION AND PART FUNCTIONS



**Ignition Switch (1):** When the ignition switch is placed in the (ON) position the engine can start. When the ignition switch is placed in the (OFF) position the engine will not start, or will turn off, if running.

1




**Brake Pedal (Red) (2):**  
Depressing the brake pedal will stop the Go Kart. Note: Always check brakes before operation

**Gas Pedal (Green) (3):** Depressing gas pedal will increase engine RPMs causing Go Kart to move forward.

2

3



**Speed limiter bolt/(4)**  
To limit the top speed, turn the throttle pedal speed regulator bolt (4) counter clockwise until the desired stop position is achieved. Re-tighten Jam nut (5) against the skid plate once adjustment is completed.

4

5


# DESCRIPTION AND PART FUNCTIONS

1



## Fuel Tank Cap (1):


To open fuel tank cap, Turn cap counter clockwise to remove. To re-install cap, turn cap clockwise until snug. Make sure cap is seated properly .



## Oil Fill plug/Dipstick (2)


Move seat completely forward to gain access to the fill plug.

To open Oil fill plug/Dipstick, turn cap counter clockwise to remove. To re-install cap, turn cap clockwise until snug. Make sure cap is seated properly



# DESCRIPTION AND PART FUNCTIONS

## SEAT ADJUSTMENT



### **⚠ WARNING**

Failure to have the seat locked in position could be hazardous.

The seat coming loose could cause the operator to lose control.

Never operate the Go Kart without the seat locked in place.

#### Seat adjustment (1)

The seat Lever is located on the left side of the go-kart. Pull up seat lever to move the seat forward or backward. Set seat location according to the size of the operator. Before operating the Go-Kart after seat adjustment, make sure the seat is locked in place and secure.

# FUEL AND OIL

## FUEL

Never use leaded gasoline in this product. Leaded fuel could affect the engine's emissions and damage the engine.


Go Kart requires clean unleaded regular gasoline with a minimum octane rating of 87 or higher.

### Gasoline/ Ethanol blends

A blend of unleaded gasoline with Ethanol, also known as GASOHOL, at or below 10% (E10 ) can be used in your Go Kart. Ethanol greater than 10% can damage your engine and will void your warranty.

### Gasoline/Methanol Blends

A blend of gasoline with Methanol of 5% or less can be used in your Go Kart. Do not use gasoline, under any circumstances, containing more than 5% Methanol, doing so will damage your engine and will void the warranty.



## ⚠ WARNING

Overfilling the fuel tank can cause the fuel to expand which can cause overflow due to the heat from the engine or sun. Spilled fuel can catch fire.

Never fill the fuel tank above the bottom edge of the filler neck.

## ⚠ WARNING

Fuel and fuel vapor are highly flammable and toxic. You can be burned or poisoned while refueling.


Before refueling make sure to follow the procedures listed:

- 1 Shut off engine, Make sure there are no flames, sparks or heat sources close by.
- 2 Make sure engine has cooled
- 3 Refuel only outdoors in a well ventilated area.
- 4 Do not smoke while refueling.
- 5 Wipe up any spills immediately.
- 6 Avoid breathing any fuel vapors.
- 7 Keep children and pets away.

## ENGINE OIL

The recommended oil for this Go Kart is SAE10W-30 motor oil, if this oil is not available, any of the oils on the chart below will work. Note the temperature requirements for each of the oils.

Quantity of oil - .63qt. (.6L).



# PRE-RIDE INSPECTION

Inspecting and checking the condition of the Go Kart before each ride is important. Following the pre-ride check list will help insure the you do not have mechanical problems which could result in injury or becoming stranded. Make sure the Go Kart is in good operating condition before each ride.

## **WARNING**

Failing to inspect and maintain your Go Kart could be hazardous.

Not following the pre-ride inspection procedures could result in losing control of the Go Kart resulting in an accident or damage to the Go Kart.

Always perform a Pre-ride inspection before operating.

## **WARNING**

Performing maintenance and checks while the engine is running could be hazardous.

You could be severely injured by moving parts or hot surfaces.

Never perform maintenance or check procedures while the engine is running with the exception of checking the ignition switch or throttle.

| WHAT TO CHECK          | CHECK FOR                                                                                                                                             |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Steering               | <ul style="list-style-type: none"><li>• Smoothness</li><li>• No restriction of movement</li></ul>                                                     |
| Brakes                 | <ul style="list-style-type: none"><li>• Correct fluid level</li><li>• Inspect hoses for leaks</li><li>• Inspect brake pads for wear.</li></ul>        |
| Tires                  | <ul style="list-style-type: none"><li>• Proper tire pressure</li><li>• Proper tread depth</li><li>• Rubber has no cracks</li></ul>                    |
| Fuel Tank              | <ul style="list-style-type: none"><li>• Enough fuel for the ride</li><li>• Fuel cap secure</li><li>• Hoses have no signs of cracks or leaks</li></ul> |
| Throttle Pedal         | <ul style="list-style-type: none"><li>• Pedal snaps back to idle when released</li><li>• Operates freely</li></ul>                                    |
| Engine Ignition switch | <ul style="list-style-type: none"><li>• Switch shuts off engine when activated.</li></ul>                                                             |
| Engine Oil             | <ul style="list-style-type: none"><li>• Correct oil level</li></ul>                                                                                   |
| Drive Chain            | <ul style="list-style-type: none"><li>• Proper tension</li><li>• Lubricated</li><li>• No excessive wear or damage</li></ul>                           |
| General Condition      | <ul style="list-style-type: none"><li>• All nuts and bolts tight</li><li>• No rattles from engine or frame while running</li></ul>                    |

# OPERATING THE GO KART

## WARNING

Carrying a passenger on this Go Kart could be hazardous

Carrying a passenger could cause loss of control resulting in severe injury or death to the operator and/or passengers.

This Go Kart is designed for one operator and no passengers.

Never allow a passenger on this Go Kart.

## WARNING

Operating this Go Kart in a irresponsible manner which includes jumping or other stunts could be hazardous.

Jumping or other stunts could result in loss of control of the Go Kart resulting in severe injury or death.

Never attempt stunts, such as jumping.

## WARNING

Operating this Go Kart on paved surfaces could be hazardous.

Operating on paved surfaces , including parking lots, sidewalks, driveways and streets can cause loss of control resulting in severe injury or death. Go Kart tires are designed for off-road use only, paved surfaces adversely affect handling and control.

Avoid operating Go Kart on paved surfaces. If you must cross a paved surface, go slow and do not make sudden turns or stops.

## WARNING

Operating a Go Kart on hills could be hazardous.

Operating a Go Kart on a hill could result in rolling over while traversing, flipping over backwards while climbing, flipping over while descending, general loss of control of the Go Kart. Any of these accidents on a hill could result in severe injury or death.

Never operate a Go Kart on steep hills.

## WARNING

Operating this Go Kart on any public road or highway could be hazardous.

You could collide with another vehicle if you operate on public roads or highways resulting in severe injury or death.

Never operate on public roads or highways.


# OPERATING THE GO KART

## HELMET, EYE PROTECTION, PROTECTIVE CLOTHING

Always wear a DOT certified helmet (1). A helmet helps protect against serious head injuries in the event of an accident. A helmet is the most important safety gear item you can wear. Consult with a motorcycle dealer for the correct size and type of helmet that is right for you.

Always wear eye protection when operating a Go Kart such as a face shield or goggles (2). While operating a Go Kart you can be hit in the eyes by any of the following: dust, branches, rocks, debris from other operators, bugs, etc. Good eye protection as well as a helmet and protective operating gear should be mandatory when operating a Go Kart.

Wear protective clothing: Long sleeve shirt (3), Gloves (4), Long pants (5), over the ankle boots (6). Operating a Go Kart exposes the operator to many hazards, wearing protective clothing can help protect the operator from injury.



### **⚠ WARNING**

Operating a Go Kart without a helmet, eye protection, and protective clothing can be hazardous

Operating a Go Kart without a helmet increases the chance of severe head injury or death in the event of an accident.

Operating a Go Kart without eye protection such as a face shield or goggles could result in severe injury in the event of an accident.

Operating a Go Kart without protective clothing; closed toe shoes, long pants, gloves, long sleeve shirt could result in severe injury in the event of an accident.

Always wear a Helmet, eye protection, long pants, long sleeve shirt, over the ankle boots and gloves while operating a Go Kart.

# OPERATING THE GO KART

## SEAT BELTS



### WARNING

Riding in this go kart without the seat belt attached properly could be hazardous

Riding the go kart without the seat belt worn increases the chance of injury or death in the event of an accident

Never operate the go kart without the seat belt worn and attached properly.

To connect the seat belt sit in the seat and buckle the lap belt. Make sure the buckle is latched properly.



# OPERATING THE GO KART

## STARTING ENGINE

To start the engine





2. Place the fuel valve (1) in the "ON" (vertical) position.

3.. If engine is cold, place the choke lever (2) in the "ON" (right) position.

4. Place the ON/OFF switch (3), located on the Steering column, in the "ON" position.

5. Pull the starter recoil cord (4) to start the engine.

6. Once engine has warmed up for a few minutes, place the choke lever (2) back to the "OFF" (left) position.



### WARNING

Starting or running the Go Kart in an enclosed area such as a garage or shed where there is no ventilation is hazardous.

Inhaling exhaust fumes from the Go Kart can cause severe injury or death.

Never start or run the Go Kart in an inclosed environment where there is no ventilation. Always start and run outdoors.

# OPERATING THE GO KART

## STARTING OFF

1. Start and warm up the engine according to the instructions in this manual.
2. Sit down in the go-kart and fasten seat belt.
3. Apply throttle gradually to start off. Practice driving the go-kart slowly on a flat dirt surface, make sure that there is plenty of room for turning.

### WARNING

Removing hands from the Steering wheel and/or feet from the floorboard while operating the Go-Kart could be hazardous.

Removing both or one hand from the Steering wheel and/or feet from the floorboard could result in loss of control of the Go-Kart resulting in severe injury or death.

Always Operate with both hands on the steering wheel and both feet on the floorboard while operating the Go-Kart.

### WARNING

Operating this Go-Kart at excessive speeds could be hazardous.

Driving at excessive speeds increases your chances of losing control of the Go-Kart, which could result in severe injury or death.

Always go at a speed that is proper for the terrain, visibility, operating conditions, operator skill, and operator experience. Always know the terrain before operating.

### WARNING

Applying the gas pedal to full throttle when starting off could be hazardous.

The Go-Kart could lurch forward causing the front wheels to leave the ground causing loss of control.

Always open the throttle gradually when starting off from a stopped position.

### WARNING

Braking while turning could be hazardous.

Braking while turning could cause the Go-Kart to slide out of control or flip over which could result in severe injury or death.

Before making a turn, slow down and release the brake.

# OPERATING THE GO KART

## CLIMBING A HILL

1. Stop and evaluate the hill before attempting to climb. Make sure the hill is not too steep, the terrain is not loose or slippery and that there are no obstacles.
2. Approach the hill at a steady speed and maintain speed throughout the climb.
3. When approaching the top of the hill, slow down.

If it is determined that the Go Kart will not make it to the top of the hill:

1. Do not try to turn the Go Kart around while operating and come back down, this could cause the Go Kart to roll over.
2. Slowly back the Go Kart down the hill while applying the brakes.

## DESCENDING A HILL

To operate the Go Kart going down a hill, follow the instructions below.

1. Stop and evaluate the hill before attempting to descend. Make sure the hill is not too steep, the terrain is not loose or slippery and that there are no obstacles.
2. Do not go down the hill on a sharp angle, this could cause the Go Kart to flip over. Instead, go straight down the hill. Apply the brakes on the way down.

## TRAVERSING A HILL

### WARNING

Traversing a hill could be hazardous.

Traversing a hill could result in losing control and flipping the Go Kart over.

This could result in severe injury or death.

Never attempt to traverse a hill that is too steep or has loose or slippery terrain.

# OPERATING THE GO KART

## SKIDDING OR SLIDING

In certain situations you may experience skidding or sliding even though the brakes are not applied. Follow the operating techniques listed below to regain control.

Front wheel begins to slide or skid:  
To regain traction, let off the throttle, do not apply the brakes.

Rear wheels begin to slide or skid:  
To regain traction, let off the throttle and brakes until control of the Go Kart is achieved, steer in the direction of the skid.

### **WARNING**

Skidding or sliding of the Go Kart could be hazardous.

Skidding or sliding could result in the Go Kart sliding into an object or overturning suddenly by regaining traction resulting in severe injury or death.

Avoid skidding or sliding. Drive to stay in control.

### **WARNING**

Applying the parking brake while operating the Go Kart could be hazardous.

Applying the parking brake while operating can cause the wheels to lock up and the Go Kart to slide out of control. The Go Kart could turn over or slide into an object. This could result in severe injury or death.

Apply the parking brake only after the Go Kart has come to a complete stop.

### **WARNING**

Applying the brakes hard on slippery surfaces could be hazardous.

Applying the brakes too hard on a slippery surface can cause the wheels to lock up and the Go Kart to slide out of control. The Go Kart could turn over or slide into an object. This could result in severe injury or death. Gently apply the brakes when on a slippery surface.

# OPERATING THE GO KART

## OPERATING THROUGH WATER

Operating through water can be hazardous, especially if it is fast moving. Make sure the water you are operating through is shallow and is not more than 5cm (2in) deep. Before crossing any water look at the terrain entering and exiting the water, the terrain should have a gradual slope with no obstacles. The bottom of the river or pool of shallow water should be hard. If you do not know the terrain or are not sure about the bottom of the pool or river, do attempt to enter. Remember to protect the environment, do not enter a river or pool of water if doing so could damage the river bank or shore line.

Brakes need to be inspected, cleaned and replaced more often if Go Kart is used in muddy, wet or sandy conditions. Inspect the Go Kart brakes regularly, have a service center clean or replace as needed.

### **WARNING**

Operating this Go Kart through fast or deep water could be hazardous;

Deep or fast moving water could cause the Go Kart to loose traction resulting in loss of control which could lead to severe injury or death.

Never operate this Go Kart in water that is more than 2in (5cm) deep. Never operate this Go Kart in fast moving water. Always check brakes after operating through water, wet brakes can reduce stopping ability. Make sure brakes are dried out. The brakes can be dried out from friction by applying the brakes multiple times.

# OPERATING THE GO KART

## OPERATING IN COLD WEATHER - PRE RIDE INSPECTION

### Brake and throttle linkages:

Cold weather requires additional pre-ride inspection of the Go Kart before operating. Inspect brake and throttle linkages making sure they operate freely and correctly. Ice and snow can cause these items to freeze. If the linkages are frozen, move the Go Kart to a warm area until these items thaw and work properly.

### Frozen tires:

Check to make sure the Go Kart tires are not frozen to the ground, if they are, pour warm water around the tires to release. Do not attempt to break the Go Kart loose using engine power, this could damage the engine and drive train.

### Brake inspection:

Start engine and allow to warm up. Check the braking ability of the Go Kart by applying the brakes on level ground while traveling at a slow (walking rate) of speed. Make sure both front and rear brakes work properly. If the front, rear, or both sets of brakes do not work, take the Go Kart to a warm area to thaw out. Once brakes are thawed, check again for proper operation, if they still do not work, take the Go Kart to a authorized service center. Do not attempt to operate the Go Kart with brakes that do not work correctly.

Preventive maintenance in cold weather operating is important. After operating in cold weather with snow, slush, water or ice, dry off the Go Kart including brake and throttle linkages. Apply the brakes several times making sure that the friction has dried off the brake pads and shoes. Cover the Go Kart with a protective cover so ice and snow cannot accumulate .

## CAUTION

Using engine power to release wheels that are frozen to the ground could damage Go Kart.

Damage to engine and drive train may occur if attempting to use engine power to free frozen wheels.

Always make sure wheels move freely before starting the Go Kart in cold weather.



## WARNING

Operating the Go Kart with wet or frozen brakes could be hazardous.

Wet or frozen brakes will increase stopping distance which could result in loss of control which could result in severe injury or death.

Always inspect the brakes before each ride by following the procedures in this manual.

# OPERATING THE GO KART

## LOAD GUIDELINES

Load guidelines including accessories:

Never exceed the maximum load capability of the Go Kart. This includes the weight of the operator and any cargo. This Go Kart is rated at 150 lbs. (68kg)..

Never allow a passenger. This Go Kart is designed for one operator and no passengers.

Do not add any accessory or cargo to the steering wheel that could impede vision or make the Go Kart harder to steer.

Make sure accessories do not get in the way of any controls of the Go Kart.

## AFTER MARKET PARTS

After market parts and accessories are available from many manufactures. We cannot confirm the quality, safety or suitability of all the accessories available. When purchasing an accessory, use caution, the handling of the Go Kart could become affected. Some accessories may make the Go Kart unsafe to operate. If you have a question about a modification or accessory, contact your dealer.

### **WARNING**

Modifications or adding accessories could be hazardous.

Modifications to the Go Kart, including adding accessories, could adversely affect the handling of the Go Kart causing an accident which could result in severe injury or death.

Never Modify this Go Kart in anyway, including adding accessories, unless the modification is a genuine certified modification or accessory approved by the manufacture. Never modify the Go Kart with improper installation. Make sure to follow all instructions recommended in the certified modification. Use only genuine parts. For questions, contact your dealer.

# MAINTENANCE

For maintenance, your Go Kart may be maintained by an authorized service center or a repair shop of your choosing.

Following the proper maintenance procedures and time table for maintenance listed in this manual is important for the safety of the operator and the life span of the Go Kart. When operating in harsh conditions, such as water, mud and dust, the maintenance procedures should be performed more often.

## **WARNING**

Failing to perform the recommended maintenance on this Go Kart could be hazardous.

Failing to perform proper maintenance on this Go Kart could result in an accident

Always perform the recommended maintenance for the Go Kart as listed in this manual.

## **WARNING**

Performing maintenance and inspection while the engine is running could be hazardous.

Performing maintenance and inspections while the engine is running could result in getting body parts or clothing caught in moving parts, or could result in touching hot items which could result in severe injury.

Shut off engine when performing maintenance and inspection checks, with the exception checking the ignition switch and throttle.

## **CAUTION**

Failing to perform recommended maintenance on this Go Kart could damage the Go Kart engine and components.

Always perform the recommended maintenance on this Go Kart as listed in this manual. Maintenance will need to be performed more often if ridden in wet, muddy or dusty conditions.

## **CAUTION**

Failing to use compatible parts with the original replacement parts could damage Go Kart.

Using parts that are of low quality could result in Go Kart breakdowns and reduce the useful life of the Go Kart.

Never use parts that are not compatible with the original parts.

# MAINTENANCE

| ITEM                                   | First 5 hours of operation                                                                                                                                    | Before each ride | Every 20 hours of operation or 1 month | Every 50 hours or 3 months | Every 100 hours or 6 months |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------|----------------------------------------|----------------------------|-----------------------------|
| Exhaust pipe nuts and muffler bolts    | T                                                                                                                                                             | I                | T                                      |                            |                             |
| Air cleaner element                    | I                                                                                                                                                             |                  | I                                      |                            |                             |
| Valve Clearance**                      |                                                                                                                                                               |                  |                                        |                            | I                           |
| Spark Plug                             |                                                                                                                                                               |                  | I                                      |                            | R                           |
| Fuel Line                              |                                                                                                                                                               | I                |                                        |                            |                             |
| Idle speed                             | I                                                                                                                                                             |                  | I                                      |                            |                             |
| Condition of throttle and brake cables | I                                                                                                                                                             | I                |                                        |                            |                             |
| Engine oil                             | R                                                                                                                                                             | I                |                                        | R                          |                             |
| Drive Chain                            | Inspect drive chain before each ride. Clean and lubricate as necessary                                                                                        |                  |                                        |                            |                             |
| Brakes                                 | I                                                                                                                                                             |                  | I                                      |                            |                             |
| Brake hose                             | I                                                                                                                                                             |                  | I                                      |                            |                             |
| Brake fluid                            | Inspect brake fluid level before each ride, if low, check brake pads for wear and brake lines and components for leaks.<br>Replace brake fluid every 2 years. |                  |                                        |                            |                             |
| Tires                                  |                                                                                                                                                               | I                |                                        |                            |                             |
| Steering                               | I                                                                                                                                                             |                  | I                                      |                            |                             |
| Front suspension                       | I                                                                                                                                                             |                  | I                                      |                            |                             |
| Rear suspension                        | I                                                                                                                                                             |                  | I                                      |                            |                             |
| Chassis nuts and bolts                 | T                                                                                                                                                             | I                | T                                      |                            |                             |

**\*\* Recommended to be performed by an authorized service center or service center of the owner's choosing.**

# MAINTENANCE

## AIR FILTER

The air cleaner element needs to be cleaned or replaced periodically (see chart for cleaning/replace-ment intervals). The air filter element will need to be cleaned more often if Go Kart is ridden in muddy, wet, or dusty conditions. A clean air filter will help the Go Kart to run at peak performance allowing better gas mileage, more power and will protect the engine from the damaging effects of dirt entering the engine.

### CAUTION


Clean air filter more frequently if Go Kart is driven in wet, muddy or dusty conditions.

Driving in the above conditions without cleaning frequently can plug up the air filter which can cause poor gas mileage, low power and cause damage to the engine.

### Air filter removal, inspection and cleaning instructions

1. Locate the air filter assembly (1)
2. Remove the Air filter assembly cover by lifting the cover over top tabs (2)
3. Remove the foam element (3).
4. Clean foam element with mild soap and water (4). Rinse and squeeze out excess water and allow to dry .

Note: If foam element (3) is damaged, replace.




# MAINTENANCE

## SPARK PLUG

This Go Kart comes equipped with an CHDY - E6TC spark plug.

To inspect the spark plug, remove the plug cap (1) then remove the spark plug (2) from the engine with the spark plug tool provided.

Inspect the plug for carbon deposits and clean if necessary with a wire brush. If plug shows excessive carbon, replace the plug.



### CAUTION

Dirt can damage the engine if it enters the spark plug hole.


Make sure the spark plug hole is covered after removing plug.

Use a thickness feeler to inspect the spark plug gap (2). The spark plug gap should be

0.6 - 0.8mm (0.024 - 0.032 in.)

Re-install the inspected plug or a new plug until finger tight. Finish tightening plug with a wrench. If spark plug is a new plug, tighten approximately 1/2 turn more with the wrench. If plug is an old plug, tighten approximately 1/8 turn more with a wrench.

CHDY - E6TC



# MAINTENANCE

## ENGINE OIL

The proper amount and grade of engine oil will have a great impact on the life of the engine. Checking the oil daily and changing the oil as listed in the maintenance schedule is the most important maintenance procedure there is for the engine.

## CHECKING THE ENGINE OIL

1. Make sure the Go Kart is on level ground
2. Check engine oil level by removing and looking at the oil plug/ dipstick (1). Oil should be close to the top of the serrated portion of the dipstick.
3. If engine oil is low, add oil until oil is at the top of the serrated portion of the dipstick. Use the correct grade of oil as listed in this manual. Do not over or under fill engine with oil, this could damage the engine.

## CHANGING THE ENGINE OIL

1. Make sure engine is warm before attempting to drain the oil. A warm engine will help the oil drain quicker.
2. Remove the oil fill plug (1)
3. Remove the drain bolt (2) located on the back bottom portion of the engine.
4. Allow the oil to drain in an appropriate container.
5. Install the drain plug and fill with the appropriate type of oil as listed in this manual. This Go Kart requires 37qt. (.35L) of engine oil.




6. Re- install fill cap, Start engine and allow to run for a few minutes, Re-check oil level and fill accordingly.

## ! WARNING

New and used oil can be hazardous

Children and pets can be harmed by swallowing new or used oil. Continuous contact with used engine oil has been found to cause skin cancer in laboratory animals


Always keep new or used oil away from children and pets.



# MAINTENANCE

## FUEL HOSE INSPECTION

Inspect the fuel hose (1) for any cracks or leaks and make sure all clamps are in place. Replace the fuel hose if any defects are found.



1

## BRAKES

This Go Kart is equipped with rear hydraulic disk brakes

### WARNING

Failing to inspect brakes before each use could be hazardous

Inspect brakes before each use according to the Pre-ride check list, make sure to follow the maintenance schedule and procedures.

## BRAKE FLUID INSPECTION

Check the brake fluid level (2) for rear brakes. If fluid level is below the lower mark, inspect the brake hoses (3) for leaks or cracks. If there are no leaks, inspect the brake pads for excessive wear. If brake pads are worn, take to a service center for replacement.

To add brake fluid, remove the lid (4). Use only DOT3 or DOT4 brake fluid



2

3





# MAINTENANCE

## Clutch lubrication

To help ensure the maximum life out of the Centrifugal clutch. It is important to clean and lubricate the clutch after every 5 hours of operation. To Clean and lubricate, follow the instructions below. Make sure engine is not running and that the engine and clutch has had time to cool.

2. Remove clutch cover (1).
3. Wipe off Centrifugal clutch (2) with a clean rag.
4. Lubricate Centrifugal clutch (2) using the same type of motor oil that is used in the engine. Place a few drops of motor oil on the drive shaft (3) where the clutch is attached. Do not oil any other portion of the clutch. **DO NOT PLACE ANY OIL IN THE LARGE HOLES IN THE CLUTCH. THE HOLES ARE FOR AIRCIRCULATION ONLY. DO NOT OIL THE INSIDE OF THE CLUTCH.**



### WARNING

Performing maintenance and inspection on the clutch assembly while the engine is running could be hazardous.

Performing maintenance and inspections on the Clutch assembly while the engine is running could result in getting body parts or clothing caught in moving parts, or could result in touching hot items which could result in severe injury.



### WARNING

Operating the Go-Kart without the clutch assembly cover in place could be Hazardous.

Operating the Go-Kart without the clutch assembly cover could result in getting body parts or loose clothing caught in moving parts which could result in severe injury.

Never Start or operate the Go-Kart without the clutch assembly cover in place.

# MAINTENANCE

## Chain and Sprocket inspection

Inspect drive chain for wear, rust, bound links, proper lubrication and proper tension.

If drive chain has a problem, correct or replace. Contact a service center for chain replacement.

A worn drive chain could also mean the sprockets may be worn. Look for the following on sprockets (1): Worn teeth, broken or damaged teeth, loose sprocket mounting nuts.


If sprockets show signs of wear, contact a service center for replacement.

## Chain Lubrication

Lubricating the chain before each ride will help to ensure maximum life of the chain and sprockets.

### Instructions for cleaning and chain lubrication:

1. Clean chain with a chain cleaner or a cleaning lubricant such as WD40.
2. Lubricate chain with chain lube.



## Chain Tension

### ⚠ WARNING

Checking chain tension while the engine is running can cause serious injury.



Always make sure engine is off before checking drive chain tension.

Check tension of drive chain (2), chain tension slack should be 0.2 - 0.5in (5 - 13mm)

## Chain tension (slack) Adjustment

1. Loosen nuts (3) on bottom of engine mounting plate.
2. Adjust chain tension by pulling engine backward (tightening) or forward (loosening) chain tension nuts (4).
3. Once the chain is at the correct tension re-tighten nut (3).
4. Re-check chain tension.

5 - 12mm  
(0.2 - 0.5in) 2



# MAINTENANCE

## TIRES

Inspect tires before each ride, this should include the following:

1. Inspect for cracks or leaks
2. Inspect tread depth. If tread depth is below 4mm (.16 in.) replace the tire.
3. Check tire pressure. Incorrect tire pressure can affect the handling, operator comfort, steering, tire life.

Tire pressure

Front tires: 14psi

Rear tires: 14psi

Tire size:

Front tires: AT 13/5-6 & AT 14/4.1-6

Rear Tires: AT 13/5-6 & AT 14/5-6

## Replacing Tires

Always replace tires with type and size listed in this manual.

Always use the correct tools when replacing tires. The bead and sometimes the rim can be damaged by using the wrong type of tools. It is usually best to have tires replaced by an authorized service center. Service centers have the correct equipment and expertise to change tires without causing damage.

Punctures to tires can usually be repaired by using plug type patches. Plug type patches cannot repair tires that have been cut. If the tire has been cut or has a puncture in a location or size that cannot be repaired, replace the tire.

Be prepared for flat tires, always carry a plug type patch kit and air pump with you.



Minimum tread  
4mm (.16 in.)



## ⚠ WARNING

Operating this Go Kart with worn tires could be hazardous.

Operating this Go Kart with worn tires will reduce traction which could result in an accident.

Never operate this Go Kart with tires that have a tread depth of less than 4mm (0.16 in.).

## ⚠ WARNING

Operating this Go Kart with improper tire sizes or pressure could be hazardous

Operating this Go Kart with improper tire sizes or pressure could result in loss of control of the Go Kart which could result in an accident.

Never operate this Go Kart with improper tire sizes or pressure.

# MAINTENANCE

## STORAGE

If the Go-Kart is left unused for an extended period of time proper storage maintenance is required.

1. Wash Go-Kart thoroughly, then wax painted parts with a non abrasive auto wax. Coat vinyl seat and rubber parts with a vinyl/rubber protectant. Note: Keep water away from air intake and muffler outlet while washing to avoid water from entering the engine and/or components.

2. Drain carburetor by placing fuel valve (1) to the off (horizontal) position and opening the drain screw (2). Allow all fuel to drain from the carburetor. Once fuel is drained, re-tighten drain screw (2).

Note: Make sure to drain fuel in a proper storage container.



3. Fill fuel tank to full with gasoline mixed with fuel stabilizer as recommended by the fuel stabilizer manufacture. Note: Fuel stabilizer can be purchased at most motorcycle shops and auto parts stores.

4. Remove spark plug and pour 1 tablespoon of motor oil in the spark plug hole. Re-install spark plug.

5. Place the starter switch to the off position and pull the start recoil cord a few times. This is to coat the inside cylinder head with oil.

6. Fill tires with correct air pressure.

7. If possible, store Go-Kart in a shed or garage with a cover to protect from dust, dirt and humidity. If the Go-Kart must be stored outdoors, cover completely with a good waterproof cover.



## Returning to service

1. Wash Go-Kart thoroughly.

Note: Keep water away from air intake and muffler outlet while washing to avoid water from entering the engine and/or components.

2. Drain engine oil and replace with fresh clean oil as listed in this manual.

3. Review this owner's manual and follow the pre-ride inspection procedures.


4. Start engine by following the starting procedures in this manual.

# MAINTENANCE

## WASHING THE GO KART

1. Wash mud and dirt off Go Kart with low water pressure from a hose.
2. Wash Go Kart using a mild detergent or car soap using a sponge, soft rag or brush. Do not use any cleaning materials that could scratch the Go Kart.

**Note:** Be careful not to allow water to enter the muffler outlet, air filter intake, brake cables or switches.




## TRANSPORTING

1. Turn the Fuel valve (1) to the "OFF" (horizontal) position. Open the fuel drain screw (2). Allow all fuel to drain from the carburetor. Once fuel is drained, re-tighten drain screw (2).

**Note:** Make sure to drain fuel in a proper storage container.

3. Transport the Go-Kart in the upright position) tied down securely.



# TROUBLESHOOTING

| Trouble                           | Possible cause                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Solution                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Engine will not start.            | <ul style="list-style-type: none"> <li>• Air filter dirty</li> <li>• Low fuel</li> <li>• Stale (old) or contaminated fuel.</li> <li>• Fuel valve is defective</li> <li>• Clogged fuel filter</li> <li>• Loose spark plug</li> <li>• Spark plug fouled or defective.</li> <li>• Spark plug gap is incorrect</li> <li>• Spark plug cap is not attached</li> <li>• Trying to start engine while applying throttle</li> <li>• Low compression</li> <li>• Problem with the electrical system</li> </ul> | <ul style="list-style-type: none"> <li>• Clean or replace air filter</li> <li>• Fill with fresh fuel</li> <li>• Have a service center flush and fill with fresh fuel.</li> <li>• Replace fuel valve</li> <li>• Replace fuel filter</li> <li>• Tighten spark plug</li> <li>• Clean or replace plug</li> <li>• Gap the plug</li> <li>• Attach spark plug cap</li> <li>• Do not apply throttle while starting engine</li> <li>• Take to a service center for repair</li> <li>• Take to a service center for diagnostics and repair</li> </ul> |
| Engine stalls or runs erratically | <ul style="list-style-type: none"> <li>• Air filter dirty</li> <li>• Low fuel</li> <li>• Stale or contaminated fuel</li> <li>• Spark plug is fouled or defective</li> <li>• Spark plug gap is incorrect</li> <li>• Spark plug cap is loose</li> <li>• Carburetor is clogged or has water in it</li> <li>• Idle is not adjusted properly</li> <li>• Problem with the electrical system</li> <li>• Low compression</li> </ul>                                                                        | <ul style="list-style-type: none"> <li>• Clean or replace air filter</li> <li>• Fill with fresh fuel</li> <li>• Have a service center flush and fill with fresh fuel.</li> <li>• Clean or replace plug</li> <li>• Gap the plug</li> <li>• Secure the spark plug cap</li> <li>• Take to a service center</li> <li>• Take to a service center</li> <li>• Take to a service center for diagnostics and repair</li> <li>• Take to a service center for repair</li> </ul>                                                                       |

# TORQUE SPECIFICATIONS

| <b>FASTNER<br/>THREAD SIZE</b>  | <b>TORQUE<br/>(ft.lbs.) / (in.lbs.)</b> | <b>TORQUE<br/>(nm)</b> |
|---------------------------------|-----------------------------------------|------------------------|
| <b>5 mm bolts and nuts</b>      | <b>39-52 in.lbs.</b>                    | <b>4.5 - 6 nm</b>      |
| <b>6mm bolts and nuts</b>       | <b>69 - 104 in. lbs.</b>                | <b>8 - 12 nm</b>       |
| <b>8mm bolts and nuts</b>       | <b>13 - 18 ft.lbs.</b>                  | <b>18 - 25 nm</b>      |
| <b>10 mm bolts and<br/>nuts</b> | <b>22 - 29 ft.lbs.</b>                  | <b>30 - 40 nm</b>      |
| <b>12 mm bolts and<br/>nuts</b> | <b>36 - 43 ft.lbs.</b>                  | <b>50-60 nm</b>        |
| <b>4 mm screws 22-30</b>        | <b>22 - 30 in.lbs.</b>                  | <b>2.5-3.4 nm</b>      |
| <b>5mm screws</b>               | <b>30 - 43 in.lbs.</b>                  | <b>3.5 - 5 nm</b>      |
| <b>6 mm hex bolts</b>           | <b>87 - 121 in.lbs.</b>                 | <b>10 - 14 nm</b>      |
| <b>8 mm hex bolts</b>           | <b>17 - 22 ft.lbs.</b>                  | <b>24 - 30 nm</b>      |
| <b>10 mm hex bolts</b>          | <b>25 - 32 ft.lbs.</b>                  | <b>35 - 45 nm</b>      |

## SPECIFICATIONS

## Engine

|                     |                                            |
|---------------------|--------------------------------------------|
| Displacement        | 98cc                                       |
| Max Power           | 1.8kw/3600rpm                              |
| Max Torque          | 3.32lb ft (4.5Nm)<br>@ 2500rpm             |
| Bore x Stroke       | (56mm x 40mm)                              |
| Starting            | Manual Pull Start                          |
| Spark Plug Type     | CHDY - E6TC                                |
| Cooling             | Air cooled                                 |
| Engine Oil Capacity | .37qt. (.35L)                              |
| Engine Oil Type     | SAE10W-30                                  |
| Fuel Capacity       | .42Gal. (1.3L)                             |
| Ignition Type       | TCINumber of<br>Cylinder Single Combustion |
| Cycle               | 4-stroke                                   |
| Top Speed           | 18.7mph (30km/h)                           |

## Transmission

|              |                    |
|--------------|--------------------|
| Type         | Automatic          |
| Drive System | Centrifugal Clutch |
| Drive        | Chain              |
| Gear Ratio   | Dual Wheel         |
|              | 8.5:1              |

## Suspension

|            |                    |
|------------|--------------------|
| Front Type | Low pressure tires |
| Rear Type  | Low pressure tires |

## Braking

|            |                |
|------------|----------------|
| Rear Brake | Hydraulic disk |
|------------|----------------|

## Tires

Front Tire Size AT13/5-6  
Rear Tire Size AT13/5-6  
Tire pressure 14psi (96.5kpa)

### Dimensions and Weights

|               |           |          |
|---------------|-----------|----------|
| Length        | 54.7in.   | (1390mm) |
| Height        | 38.3 in.  | (975mm)  |
| Width         | 32 in.    | (815mm)  |
| Wheelbase     | 36.2in.   | (920mm)  |
| Gd. Clearance | 2.2in.    | (55mm)   |
| Vehicle Wt.   | 136.6 lbs | (62kg)   |
| Weight Cap.   | 150 lbs.  | (68kg)   |

## Fuel

**Gas Tank Capacity** .42gal. (1.3L)  
**Fuel type** Unleaded 87 octane  
 or higher

# VEHICLE IDENTIFICATION NUMBER LOCATION

The Vehicle identification number is needed when calling for parts, service center help or when registering your Go Kart. Locate the number and list the number below for your reference.



The 17 digit Vehicle Identification Number (VIN) is stamped on the left rear bumper support frame on the go-kart.

**Vehicle Identification  
Number:**

|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|
|  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |  |
|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|--|

**VIN #**