

# AUDI R8 SPYDER

## BATTERY-POWERED RIDE ON



## Owner's Manual

### with Assembly Instructions

Styles and colo(u)rs may vary.  
Made in China.

The owner's manual contains important safety information as well as assembly, use and maintenance instructions.

The Ride-on Car must be assembled by an adult who has read and understands the instructions in this manual.

Keep the package away from children and dispose of properly before use.

**Keep this manual for future reference.**

Congratulation On the purchase of your new AUDI Ride-On.

This ride-on car will provide your child with many miles of riding enjoyment. To help assure you and your rider a safe ride we ask you to please read this manual carefully, and keep it for future reference.

Follow the recommendations in this manual, they are designed to improve the safety and operation of your ride-on car and it's rider.

**Audi R8 Spyder Electric Ride-on manufactured by Zhejiang Jiajia Ride-on Co.,Ltd. (Xincang Industrial Zone, Xincang Town, Pinghu City, Zhejiang Province, China). Trademarks, design patents and copyrights are used with the approval of owner AUDI AG.**

|                |                    |           |
|----------------|--------------------|-----------|
| <b>Battery</b> | 6V7Ah*1 or 6V10 *1 | 6V7Ah*2   |
| <b>Charger</b> | 6V1000mA           | 12V1000mA |

***Suitable age:*** 37~96 Months

***Load Capacity:*** Under 30 kgs

***Speed:*** 1WD: 2.5 km/h      2WD:2.5~5 km/h


***Size of car:*** 123 x 71 x 49 CM

***Power way:*** Charging type

***Charge time:*** 8 ~ 12 hours

## Parts List | 2

| PART NO. | PART NAME             | Q'ty (pcs) |     | REMARKS                                            |
|----------|-----------------------|------------|-----|----------------------------------------------------|
|          |                       | 1WD        | 2WD |                                                    |
| 1        | Vehicle body          | 1          |     |                                                    |
| 2        | Gear box              | 1          | 2   | 2WD One labeled "L", and the other one labeled "R" |
| 3        | Driving wheel         | 1          | 2   |                                                    |
| 4        | Normal wheel          | 3          | 2   |                                                    |
| 5        | Bush                  | 3          | 2   |                                                    |
| 6        | Ø12 washer            | 8          | 6   |                                                    |
| 7        | Motor hood            | 1          | 2   |                                                    |
| 8        | Ø4x12 flat head screw | 4          | 8   |                                                    |
| 9        | Lock nut              | 4          |     |                                                    |
| 10       | Hubcap                | 4          |     |                                                    |
| 11       | M5x16 machine screw   | 2          |     | for seat                                           |
| 12       | Seat                  | 1          |     |                                                    |
| 13       | Mirror                | 2          |     | Left and right                                     |
| 14       | Steering Wheel        | 1          |     |                                                    |
| 15       | M5x35 machine screw   | 1          |     | Placed on the steering wheel                       |
| 16       | Ø5 nut                | 1          |     | Placed on the steering wheel                       |
| 17       | Charger               | 1          |     |                                                    |
| 18       | Spanner               | 2          |     |                                                    |
| 19       | Remote controller     | 1          |     | IF EQUIPPED, for R/C type only                     |
| 20       | Rear axle             | 1          |     |                                                    |
| 21       | Windshield            | 1          |     |                                                    |




HINT: Some parts shown are assembled on both sides of vehicle

 **WARNING!**

- **CHOKING HAZARD** - Small parts. Not suitable for children under 36 months. The product contains small parts, keep children away when assembling.
  - **ADULT ASSEMBLY REQUIRED.**
  - Always remove protective material and poly bags and dispose before assembly.
- 
- Make sure that the power switch is **turned “OFF”** before assembling the ride-on.
  - Before first time use, charge the battery for at least 4 to 6 hours.
  - Assembly tools required:



Screwdriver  
(not included)




Spanner


**BATTERY INFORMATION**

- Non-rechargeable batteries are not to be recharged.
- Rechargeable batteries are to be removed from the toy before being charged.
- Rechargeable batteries are only to be charged under adult supervision.
- Different types of batteries or new and used batteries are not to be mixed.
- Batteries are to be inserted with the correct polarity.
- Exhausted batteries are to be removed from the toy.
- The supply terminals are not to be short-circuited.


**HINT:** If your vehicle is *Two Wheels Driving Type*, see the next page please.



- Turn the vehicle body downside up.
  - Remove all the parts from the rear axle.
1. Slide the **gear box** onto the **rear axle (Left Side)**. Keep the **motor** and the **connector** on the gear box through the larger hole on the rear vehicle and out where the battery sits.
  2. Slide the **driving wheel** onto the rear axle. And keep the **driving wheel** match with the **gear box**.
  3. Slide the **Ø12 Washer** onto the **rear axle**.
  4. Tighten a **Lock nut** to the end of the **rear axle** with a spanner.



5. Slide the **Ø12 Washer** onto the **rear axle (Right Side)**.
6. Insert the bush into the hole in the center of the normal wheel.
7. Slide the **Normal wheel** onto the rear axle.
8. Slide the **Ø12 Washer** onto the **rear axle**.
9. Tighten a **Lock nut** to the end of the **rear axle** with a spanner. **HINT: An extra spanner has been provided to hold the Lock Nut on the other side of the rear axle while tightening the Lock Nut on the other side.**
10. Fit the **hubcaps** to the wheel.




- Turn the vehicle body downside up.
  - Remove all the parts from the rear axle.
1. Slide the **gear box** onto the **rear axle**. “R” labeled gear box should be fit to the “R” side of vehicle body; “L” labeled gear box should be fit to “L” side of vehicle body. Keep the **motor** and the **connector** on the gear box through the larger hole on the rear vehicle and out where the battery sits.
  2. Slide the **driving wheel** onto the rear axle. And keep the **driving wheel** match with the **gear box**.
  3. Slide the **Ø12 Washer** onto the **rear axle**.
  4. Tighten a **Lock nut** to the end of the **rear axle** with a spanner.

**Repeat the above procedure to assemble the other driving wheel.**

**HINT: An extra spanner has been provided to hold the Lock Nut on the other side of the rear axle while tightening the Lock Nut on the other side.**

5. Fit the **hubcaps** to the wheel.




Remove all the parts from the front axle.

1. Slide a **Ø12 washer** onto the **front axle**.
2. Slide a bush into the hole in the center of the normal wheel.
3. Slide the **normal wheel** onto the rear axle. And keep the **normal wheel** match with the bush.
4. Slide a **Ø12 washer** onto the **front axle**.
5. Tighten a **Lock nut** to the end of the **front axle** with a spanner.
6. "Snap" the **hubcap** to the wheel.

**Repeat the above procedure to assemble the other front wheel.**

**HINT:** If the steering wheel of your vehicle equipped with the sound function, please follow the steps 1~4 to add the batteries (Not Included), and refer to the battery information on page 4.


1. With a screwdriver remove the **screw** on the **battery cover** located in the center of the steering wheel.
2. Remove the **battery cover** from the top of the **battery compartment**.
3. Insert two **AA batteries** in their correct polarities.
4. Place the **battery cover** over the **battery compartment** and fasten with the **screw** you removed in step one.




### Attache the Steering Wheel

Remove the **M5x35 machine screw** and **Ø5 nut** from the **steering wheel**.

5. Place the **steering wheel** over the **steering column**, protruding from the middle of the **steering wheel base**.
6. Align the **holes** on each side of **steering wheel** with the holes at the **end of the steering column**.
7. Fasten a **nut** on the opposite end of the **screw** to secure the **steering wheel** to the **steering**



Rear Top View




## 1WD

1. Plug the **Vehicle Connector** into the **Motor Connector** on body as shown above.
2. Plug the **Red fuse connector** into the **terminal on battery**.

## 2WD

1. Plug the **Vehicle Connector** into the **Motor Connector** on body as shown above. Repeat for the other side.
2. Plug the **Red fuse connector** into the **terminal on battery**.




## 1WD



1. Fit the **motor hood** on the motor.
2. Tighten four **Ø4x12 flat head screws** to secure it.

## 2WD

1. Fit the **motor hood** on the motor.
2. Tighten four **Ø4x12 flat head screws** to secure it.  
Repeat the above steps for the other **Motor hood**.

1. Fit the **tabs** on the back of seat into the slots on the rear vehicle.
2. Tighten two **M5x16 machine screws** to secure it with a screwdriver.





1. Fit tabs on the windshield into the slot located on the front vehicle. Push until you hear it click into place.
2. Fit the **mirror** into the hole on side of vehicle. Repeat for the other side.



# WARNING!

## PREVENT INJURIES AND DEATHS:

- **NEVER LEAVE CHILD UNATTENDED. DIRECT ADULT SUPERVISION IS REQUIRED.** Always keep child in view when child is in vehicle.
- This toy should be used with caution since skill is required to avoid falls or collisions causing injury to the user or third parties.
- Protective equipment should be worn.
- Never use in roadways, near cars, on or near steep inclines or steps, swimming pools or other bodies of water.
- Always wear shoes.
- Always sit on the seat.
- Not to be used in traffic.
- This toy is unsuitable for children under 36 months due to its maximum speed; Maximum user weight is 30 kgs.
- This toy has no brake.

## Rules for Safe Riding


- Keep Children within Safe Riding Areas:
  - Never use in roadway, near motor vehicles, on lawn space, on or near steep inclines or steps, swimming pools or other bodies of water;
- Use the toy only on flat surfaces. Such as inside your house, garden or playground.
- Never use in the dark. A child could encounter unexpected obstacles and have an accident. Operate the vehicle only in the daytime or a well-lit area.
- It is prohibited to change the circuit or add other electric parts
- Inspect wires and connections of the vehicle periodically.
- Do not let any child touch the wheels or be near them when the car is moving .
- This vehicle has adjustable play seat belts. Please instruct children how to tie the safety belt before using, guarantee the security.



Use the vehicle on generally level ground ONLY!

DO NOT Use the vehicle on Lawn space!

Your vehicle may be equipped with the Multi-Function dash, see the next page please!



**! IMPORTANT**  
Always stop vehicle when changing the speed or direction to avoid damage the gears and motor.

1. **Power Switch:** Turns the vehicle on and off.
2. **Forward/reverse switch:** Changes the direction that vehicle moves from forward to reverse.
  - To move the car forward, rock the switch to “forward” position.
  - To move the car backward, rock the switch to “reverse” position.
3. **Sounds buttons (IF EQUIPPED):** Press for sounds playing.
4. **Volume knob (IF EQUIPPED):** Turn the knob clockwise to increase the volume; Turn the knob counterclockwise to decrease the volume.
5. **Foot pedal:** Applies power (speed) to the vehicle.
  - To move the car, press the pedal down.
  - To brake or slow down, release pressure from the pedal.
6. **Auxiliary input (IF EQUIPPED):** Allow the audio from your portable music player or phone to be played through the vehicle speakers.
7. **Digital voltmeter (IF EQUIPPED):** See <Charging>, page 18.
8. **High/Low speed switch (IF EQUIPPED):** The switch operates the vehicle to move forward in low or high speed.
9. **Device input (IF EQUIPPED):** Allow the audio from the portable device to be played through the vehicle speakers. MP3 format ONLY.
  - ▶ II / V+: Press to play and pause, long press to increase the volume.
  - ▶ I / V-: Press to play next track, long press to decrease the volume.




## ADVANCED USE - High speed Drive

Make sure your child knows how to steer, how to start and stop the vehicle and knows the rules for safe driving. The vehicle can be driven at a maximum of 2.5~5 km/h.



**WARNING:**

**ADULT OPERATING REQUIRED!**



**The remote control has precedence over foot pedal operation.  
(The foot pedal won't work while you operate the Remote Controller)**

### 1. Connect button (build connection)

Lift the battery compartment door on the back of the controller and insert two AAA (LR03) batteries. **NOTE: Batteries not included. Refer to the battery information on page 4.**

Press and hold the connect button for 3 seconds, the low-speed indicator flashes, mean that the remote controller is in the connected state. Then power on the vehicle:

The low-speed indicator goes to long bright, means the connection successful.

If the low-speed indicator no response, means the connection failed. Turn off the remote controller (by removing the batteries) and the vehicle. And try again.

### 2. Brake button

Press the button to stop the vehicle, press it again to release the brake.


### 3. Speed select button

The switch operates the vehicle to move in low, normal or high speed.

**HINT: The vehicle is designed to operate in low speed only in reverse.**

### NOTE:

- Leave the remote controller idling for about 10 seconds, it will shut down automatically.
- After you replacing the batteries of the remote controller, please rebuild the connection. (step 1)



**NOTE:**

Please close the door and ensure the lock snap into place when riding for safety consideration.

**ONLY AN ADULT CAN CHARGE AND RECHARGE THE BATTERY!**

# **WARNING!**




## • **PREVENT FIRE AND ELECTRIC SHOCK:**

- Use the only rechargeable battery and charger supplied with your vehicle. NEVER substitute the battery or the charger with another brand. Using another battery or charger may cause a fire or explosion.
- Do not use the battery or charger for any other product. Overheating, fire or explosion could occur.
- NEVER modify the electric circuit system. Tampering with the electric system may cause a shock, fire or explosion or may permanently damage the system.
- Do not allow direct contact between battery terminals. Fire or explosion can occur.
- Do not allow any type of liquid on the battery or its components.
- Explosive gasses are created during charging. Do not charge near heat or flammable materials. Charge the battery in a well-ventilated area ONLY.
- NEVER pick up the battery by the wires or charger. Damage can occur to the battery and may cause a fire. Pick up the battery by the case ONLY.
- Charge the battery in a dry area ONLY.
- Battery posts, terminals and related accessories contain lead and lead compounds, chemicals known to the State of California to cause cancer and reproductive harm. **Wash hands after handling.**
- Do not open the battery. Battery contains lead acid and other materials that are toxic and corrosive.
- Do not open the charger. Exposed wiring and circuitry inside case may cause electric shock.
- Only adults may handle or charge the battery. NEVER allow child to handle or charge the battery. Battery is heavy and contains lead acid (electrolyte).
- Do not drop the battery. Permanent damage to the battery could occur or cause serious injury.
- Before charging the battery, check for wear or damage to the battery, charger, its supply cord and the connectors. DO NOT charge the battery if any damage to parts has occurred.
- Do not allow the battery to drain completely. Recharge the battery after each use or once a month if not used regularly.
- Do not charge battery upside down.
- Always secure the battery with the bracket. Battery can fall out and injure a child if vehicle tips over.

- The POWER SWITCH must be turned in **OFF** position when charging.
- Before the first use, you should charge the battery for 4-6 hours. Do not recharge the battery for more than 10 hours to avoid overheating the charger.
- When the vehicle begins to run slowly, recharge the battery.
- After each use or once a month minimum recharge time as 8 to 12 hours, less than 20 hours at most.

- If your ride-on with a **Digital voltmeter(IF EQUIPPED)**, the magnitude of voltage will tell you how much power is remaining in the battery when you must recharge the battery. Make sure the vehicle is stop!

| BATTERY                                               | MAGNITUDE OF VOLTAGE | BATTERY STATE                                                      |
|-------------------------------------------------------|----------------------|--------------------------------------------------------------------|
| 6V4Ahx1, 6V7Ahx1<br>6V10Ahx1                          | $\geq 6.6$           | The battery is full.                                               |
|                                                       | 6.5~6.3              | The vehicle can work normally.                                     |
|                                                       | $\leq 6.2$           | The battery needs to be charge.                                    |
| 6V4Ahx2, 6V7Ahx2,<br>6v10Ahx2,12V7Ahx1,<br>12V10Ah x1 | $\geq 13.2$          | The battery is full.                                               |
|                                                       | 13.1~12.6            | The vehicle can work normally.                                     |
|                                                       | $\leq 12.5$          | <b>STOP</b> operating the vehicle, the battery needs to be charge. |



1. Plug the charger port into the input socket. (the socket is below the seat)
2. Plug the charger plug into a wall outlet. The battery will begin charging.



## WARNING!

This product with **Charging Protection**: when charging, all functions will be cut off! Only an adult can charge and recharge the battery!

The battery features a thermal fuse with a reset fuse that will automatically trip and cut all power to the vehicle if the motor, electric system or battery is overloaded. The fuse will reset and power will be restored after the unit is turned OFF for 20 seconds and then turned ON again. If the thermal fuse trips repeatedly during normal use, the vehicle may need repair. **Contact your distributor please.**

To avoid losing power, follow these guidelines:

- Do not overload the vehicle.
- Do not tow anything behind the vehicle.
- Do not drive up steep slopes.
- Do not drive into fixed objects, which may cause the wheels to spin, causing the motor to overheat.
- Do not drive in very hot weather, components may overheat.
- Do not allow water or other liquids to come in contact with the battery or other electric components.
- Do not tamper with the electric system. Doing so may create a short, causing the fuse to trip.

### Battery Replacement and Disposal



The battery will eventually lose the ability to hold a charge. Depending on the amount of use, and varying conditions, the battery should operate for one to three years. Follow these steps to replace and dispose the battery:

1. Remove the car seat.
2. Disconnect the battery connectors.
3. Remove the battery bracket.
4. Remove the battery cover.
5. Carefully lift the battery.
  - Depending on the condition of the battery (i.e.: leakage) you may want to wear protective gloves before removal.
  - Do not lift the battery by its connectors or cables.
6. Place the dead battery in a plastic bag.

**Important!** Recycle the dead battery responsibly. The battery contains lead acid (electrolyte) and must be disposed of properly and legally. It is illegal in most areas to incinerate lead acid batteries or dispose of them in landfills. Take it to a federal or state-approved lead acid battery recycler, such as local automotive battery retailer. Do not throw the battery away with your regular household waste!

7. Replace the battery and reconnect the connectors.
8. Replace the metal battery bracket.
9. Replace the seat.

| Problem                                                        | Possible Cause                                  | Solution                                                                                                                                                     |
|----------------------------------------------------------------|-------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Vehicle does not run                                           | Battery low on power                            | Recharge battery.                                                                                                                                            |
|                                                                | Thermal fuse has tripped                        | Reset fuse, see <Fuse>                                                                                                                                       |
|                                                                | Battery connector or wires are loose            | Check that the battery connectors are firmly plugged into each other. If wires are loose around the motor <b>contact your distributor please.</b>            |
|                                                                | Battery is dead                                 | Replace battery, <b>contact your distributor please.</b>                                                                                                     |
|                                                                | Electrical system is damaged                    | <b>Contact your distributor please.</b>                                                                                                                      |
|                                                                | Motor is damaged                                | <b>Contact your distributor please.</b>                                                                                                                      |
| Vehicle does not run very long                                 | Battery is under charged                        | Check that the battery connectors are firmly plugged into each other when recharging                                                                         |
|                                                                | Battery is old                                  | Replace battery, <b>contact your distributor please.</b>                                                                                                     |
| Vehicle runs sluggishly                                        | Battery low on power                            | Recharge battery, <b>contact your distributor please.</b>                                                                                                    |
|                                                                | Battery is old                                  | Replace battery, <b>contact your distributor please.</b>                                                                                                     |
|                                                                | Vehicle is overload                             | Reduce weight on vehicle. Maximum user weight is 30 kgs.                                                                                                     |
|                                                                | Vehicle is being used in harsh conditions       | Avoid using vehicle in harsh conditions ,see <Safety>.                                                                                                       |
| Vehicle needs a push to go forward                             | Poor contact of wires or connectors             | Check that the battery connectors are firmly plugged into each other. If wires are loose around the motor, <b>contact your distributor please.</b>           |
|                                                                | "Dead Spot" on motor                            | A dead spot means the electric power is not being delivered to the terminal connection and the vehicle needs repair. <b>Contact your distributor please.</b> |
| Difficult shifting from forward to reverse or vice-versa       | Attempting to shift while the vehicle is motion | Completely stop the vehicle and shift, see <Use Your Ride-On>                                                                                                |
| Loud grinding or clicking noises coming from motor or gear box | Motor or gears are damaged                      | <b>Contact your distributor please.</b>                                                                                                                      |
| Battery will not recharge                                      | Battery connector or adapter connector is loose | Check that the battery connectors are firmly plugged into each other.                                                                                        |
|                                                                | Charger not plugged in                          | Check that the battery charger is plugged into a working wall outlet.                                                                                        |
|                                                                | Charger is not working                          | <b>Contact your distributor please.</b>                                                                                                                      |
| Charger feels warm when recharging                             | This is normal and not a cause for concern      |                                                                                                                                                              |

Completely read through this manual and the troubleshooting guide table before calling. If you still need help resolving the problem **Contact your distributor please.**

- It is parents' responsibility to check main parts of the toy before using, Must regularly examine for potential hazard, such as the battery, charge, cable or cord, plug, screws are fastening enclosure of other parts and that in the event of such damage, the toy must not be used until that damage had been properly removed.
- Make sure the plastic parts of the vehicle are not cracked or broken.
- Occasionally use a lightweight oil to lubricate moving parts such as wheels.
- Park the vehicle indoors or cover it with a tarp to protect it from wet weather.
- Keep the vehicle away from sources of heat, such as stoves and heaters. Plastic parts may melt.
- Recharge the battery after each use. Only an adult can handle the battery. Recharge the battery at least once a month when the vehicle Raider is not being used.
- Do not wash the vehicle with a hose. Do not wash the vehicle with soap and water. Do not drive the vehicle in rainy or snowy weather. Water will damage the motor, electric system and battery.
- Clean the vehicle with a soft, dry cloth. To restore shine to plastic parts, use a non-wax furniture polish. Do not use car wax. Do not use abrasive cleaners.
- Do not drive the vehicle in loose dirt, sand or fine gravel which could damage the moving parts, motors or the electric system.
- When not using, all the electrical source should be turn off. Turn off the power switch and disconnect the battery connection.

Our products are suitable for  
ASTM F963; GB6675; EN71 and EN62115 standard.